



Product:	Neolution®Air	 
REF:	255V	
Manufacturer:	DACH Schutzbekleidung GmbH & Co. KG	
Classification:	▪ Category III Personal Protective Equipment accordingly Regulation (EU) 2016/425	
Protection class:	Particle filtering half mask FFP2 NR D accordingly EN 149:2001+A1:2009. Very good skin compatibility scientifically proven by testing accordingly EN ISO 10993-5 (cytotoxicity), EN ISO 10993-10 (sensitization) and EN ISO 10993-23 (irritation): The materials used are not cytotoxic, not sensitizing and not irritating.	
Materials:	<ul style="list-style-type: none">▪ Mask body: Polypropylene nonwoven▪ Head strap: textile elastic made of polyester and elastane, free from natural latex▪ Nose clip: metal wire covered with plastic▪ Valve: Polypropylene	
Product Description:	<p>The three-part respirator Neolution®Air impresses with high-quality materials that guarantee the wearer maximum comfort. High-tech filter material generates a high filtering performance against solid and liquid aerosols with extremely low breathing resistance.</p> <p>Due to the three movable parts, the mask follows the jaw movements during speech. This ensures a constant tight fit.</p> <p>Textile headgear ensures a secure fit of the mask to the face. The straps fit comfortably on the head without pinching or pulling hair.</p> <p>Maximum protection even under extreme conditions: for disposable masks voluntary dolomite dust clogging test passed!</p>	

Product performance:	Product performance according to EN 149:2001+A1:2009						
	Filter efficiency						
	Class	Requirement			Test result		
		Maximum penetration			Actual penetration		
		NaCl 95 l/min	Paraffin oil 195 l/min		NaCl 95 l/min	Paraffin oil 95 l/min	
	FFP2 NR D	6 %	6 %		0,84 %	<6 %	
	Breathing resistance						
	Class	Requirement			Test result		
		Maximum breathing resistance (mbar)			Actual breathing resistance (mbar)		
		Inhalation		Exhalation	Inhalation		Exhalation
		30 l/min	95 l/min	160 l/min	30 l/min	95 l/min	160 l/min
	FFP2 NR D	0,7	2,4	3,0	0,3	1,0	1,15
	Leakage test						
	Class	Requirement			Test result		
		Maximum total inward leakage (%)	Minimum Protection factor (Fit Factor)		Total inward leakage (%) ¹	Protection factor (Fit Factor) ^{1,2}	
	FFP2 NR D	8	10		0,82	122	
	¹ The leakage and protection factor values were determined as mean values with two test persons under laboratory conditions and are for reference only. The data does not represent the actual leakage of a person at the workplace and does not replace an individual fit test. ² The fit factor (protection factor) indicates the ratio between the particle concentration outside the mask and the particle concentration inside the mask.						
Carbon dioxide content of the inhaled air							
Class	Requirement (max.)			Test result			
FFP2 NR D	1 %			0,58 %			
Packaging and variants:	Packaging			Quantity	GTIN		



	Box	20 pcs.	4049825006565
	Shipping carton	120 pcs.	4049825506553
	Pallet	5760 pcs.	
Use:	For single use. Read the instructions for use before use.		
Storage:	Store in a dry place without direct sunlight in the original packaging (see packaging). If the storage conditions are observed, the product has a storage life of 5 years (see labeling on the product).		
Environmental sustainability and disposal:	In the case of contaminated products, the type and extent of contamination determines the disposal, and the applicable laws and regulations of the relevant country must be followed. A non-contaminated product can be thermally recycled or disposed of in landfills without releasing toxic substances.		