


Product:	Neolution®Air Loop				
REF:	253V				
Manufacturer:	DACH Schutzbekleidung GmbH & Co. KG				
Classification:	▪ Category III Personal Protective Equipment accordingly Regulation (EU) 2016/425				
Protection class:	Particle filtering half mask FFP2 NR D with valve accordingly EN 149:2001+A1:2009. Very good skin compatibility scientifically proven by testing accordingly EN ISO 10993-5 (cytotoxicity), EN ISO 10993-10 (sensitization) and EN ISO 10993-23 (irritation): The materials used are not cytotoxic, not sensitizing and not irritating.				
Materials:	<ul style="list-style-type: none">▪ Mask: Polypropylene nonwoven▪ Ear loops: textile elastic made from polyester and elastane▪ Nose clip: metal wire covered by plastic▪ Valve: Polypropylene Mask is free from natural latex.				
Product description:	<p>The three-part respirator Neolution®Air Loop impresses with high-quality materials that guarantee the wearer maximum comfort. High-tech filter material generates a high filtering performance against solid and liquid aerosols with extremely low breathing resistance.</p> <p>Due to the three flexible mask parts, the mask follows the jaw movements when speaking. This ensures a constant tight fit.</p> <p>Quick and secure donning and doffing thanks to elastic ear loops. The thick ear loops fit comfortably around the ear without cutting in.</p> <p>Maximum protection even under extreme conditions: for disposable masks voluntary dolomite dust loading test passed!</p>				
Product performance:	Product performance accordingly EN 149:2001+A1:2009				
	Filter efficiency				
	Class	Requirement		Test result	
		Maximum penetration		Actual penetration	
		NaCl 95 l/min	Paraffin oil 95 l/min	NaCl 95 l/min	Paraffin oil 95 l/min

	FFP2 NR D	6%	6%	0,84%	<6%		
	Breathing resistance						
	Class	Requirement			Test result		
		Maxium breathing resistance (mbar)			Actual breathing resistance (mbar)		
		Inhalation		Exhalation	Inhalation		Exhalation
		30 l/min	95 l/min	160 l/min	30 l/min	95 l/min	160 l/min
	FFP2 NR D	0,7	2,4	3,0	0,3	1,0	1,15
	Leakage test						
	Class	Requirement			Test result		
		Maximum total inward leakage (%)	Minimum Protection factor (Fit Factor)	Total inward leakage (%) ¹		Protection factor (Fit Factor) ^{1,2}	
	FFP2 NR D	8	10	3,43		29,2	
	¹ The leakage and protection factor values were determined as mean values with 3 test persons under laboratory conditions and are for reference only. The data does not represent the actual leakage of a person at the workplace and does not replace an individual fit test. ² The fit factor (protection factor) indicates the ratio between the particle concentration outside the mask and the particle concentration inside the mask.						
	Carbon dioxide content of inhalation air						
	Class	Requirement (max.)			Test result		
	FFP2 NR D	1%			0,58%		
Packaging and Variants	Packaging		Quantity		GTIN		
	Box		20 pcs.		4049825006572		
	Carton		120 pcs.		4049825506560		
	EURO Pallet		6480 pcs.				
Use:	For single use. Read the instructions before use.						

Storage:	<p>Store in a dry place without direct sunlight in the original packaging (see packaging).</p> <p>If the storage conditions are observed, the product has a storage life of 5 years (see labelling on the product).</p>
Environmental sustainability and disposal:	<p>In the case of contaminated products, the nature and extent of the contamination determines the disposal, following the applicable laws and regulations of the relevant country.</p> <p>A non-contaminated product can be thermally recycled or disposed of in landfills without releasing toxic substances.</p>